



ALLIED
MOULDED
PRODUCTS, Inc.

222 N. Union St.
Bryan, OH 43506
419-636-4217

www.alliedmoulded.com

9305 AND 9355 FIXTURE SUPPORT BOX MOUNTING
INSTRUCTIONS

FOR MAXIMUM 50 LBS. FIXTURE WEIGHT IN CEILING
APPLICATIONS

WHEN FASTENED TO FRAMING THROUGH BOTTOM HOLES. (*)

OR

FOR MAXIMUM 15 LBS. FIXTURE WEIGHT

WHEN INSTALLED IN WALLS WITH FLANGE SCREWS. (*)

INSTALLATION
INSTRUCTIONS
CEILING
APPLICATION
50 LB. MAX.
FIXTURE

1. Locate support joist for desired box and ceiling height.
NOTE: Bottom of the box must be in contact with the support joist.
2. Insert two Pan Head #8 screws (at least 3/4" long with 5/16" diameter head) through rivet button holes in bottom of box and tighten until box is secure.
3. Pull wire into box.
4. Install ceiling surface material.



INSTALLATION
INSTRUCTIONS
WALL
APPLICATION
15 LB. MAX.
FIXTURE

1. Cut/Drill 3 5/8" Dia. hole through secure wall backing.
NOTE: Wall substrate must be capable of supporting the box with the rated load.
2. Pull wire past K-Klump into box if wire would not be accessible later.
3. Insert four Pan Head #8 screws (at least 3/4" long) through holes in flange of box and tighten until box is secure.
4. Pull slack wire into box.



(*) TESTED AND LISTED PER UL 514C, SECTION 29.4

Last Edited: 6/17/2011

17-CEILINGINS