



Product Info

Brand: ULTRALINE® **UPC:** 85339978183 **UNSPSC: 39121324 Carton Quantity:** 1 Carton Weight: 5 lbs

Country of Origin: United States of America Color: Gray (RAL 7035) with clear cover Patents: U.S. Patent No. 7,572,975

Material: ULTRAGUARD® Fiberglass reinforced polyester compression molded SMC box and clear polycarbonate cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

AMU1086CCTF

10"x8"x6" ULTRALINE® fiberglass wall mount enclosure assembly with hinged clear cover and stainless-steel twist latch

Availability:

In-Stock (Normally ships within 2-4 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

Enclosure Type: JIC Size

Cover Type: Clear Polycarbonate Closure Type: Metal Twist Latch

Mounting Description: Nonmetal flange fastened to

back side brass inserts

Box Features: Installation Type: Height: 10.04 in

Width: 8.26 in **Depth:** 6.13 in Usable Depth: 6.1 in

Volume: 569 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive









▼ WARNING – PROP 65 Click here for more information!