

# **Product Info**

Brand: POLYLINE®

UPC: 85339993377

UNSPSC: 39121324

Carton Quantity: 1

Carton Weight: 5 lbs

Country of Origin: United States of America

Color: Gray (RAL 7035) with clear cover

Patents: U.S. Patent No. 7,572,975

Material: Polycarbonate box and clear polycarbonate cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

# AMP1206CCNLF

12"x10"x6" POLYLINE® polycarbonate wall mount enclosure assembly with hinged clear cover and nonmetal snap latch

## Availability:

**In-Stock** (Normally ships within 2-4 business days after receipt of order) – Lead times may be delayed temporarily due to Covid-19 related events.

Enclosure Type: JIC Size

Cover Type: Clear Polycarbonate

Closure Type: Nonmetal Snap Latch

**Mounting Description:** Nonmetal flange fastened to back side brass inserts

Box Features:

Installation Type:

Height: 11.93 in

Width: 10.15 in

**Depth:** 5.94 in

Usable Depth: 6.06 in

Volume: 829 cu in

# Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

## Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

## Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with: 1. EN / IEC 60204-1 and 60529 Type IP66 2. RoHS directive



**WARNING** – PROP 65 Click here for more information!