



# **Product Info**

Brand: ULTRALINE®

UPC: 85339959410

UNSPSC: 39121324

Carton Quantity: 1

Carton Weight: 6 lbs

Country of Origin: United States of America

Color: Gray (RAL 7035) with clear window

Patents: U.S. Patent No. 7,572,975

**Material:** ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and cover with bonded clear polycarbonate window

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

## AMU1206WF

12"x10"x6" ULTRALINE® fiberglass wall mount enclosure assembly with 4-screw lift-off window cover **Availability: Made to order**; normally ships within 2 weeks after receipt of order – Lead times may be delayed temporarily due to Covid-19 related events.

Enclosure Type: JIC Size

Cover Type: Opaque with Viewing Window

Closure Type: 4-Screw Lift-Off

**Mounting Description:** Nonmetal flange fastened to back side brass inserts

**Box Features:** 

Installation Type:

Height: 12.05 in

Width: 10.27 in

Depth: 6 in

Usable Depth: 6 in

Volume: 867 cu in

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

### Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

#### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with: 1. EN / IEC 60204-1 and 60529 Type IP66 2. RoHS directive



**WARNING** – PROP 65 Click here for more information!