



# **Product Info**

Brand: POLYLINE®

UPC: 85339993568

**UNSPSC:** 39121324

**Carton Quantity:** 1

Carton Weight: 8 lbs

Country of Origin: United States of America

**Color:** Gray (RAL 7035)

Patents: U.S. Patent No. 7,572,975

Material: Polycarbonate box and cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

## AMP1426HF

14"x12"x6" POLYLINE® polycarbonate wall mount enclosure assembly with 2-screw hinged cover **Availability:** 

**In-Stock** (Will ship within 2 business days after receipt of order) – Lead times may be delayed temporarily due to Covid-19 related events.

Enclosure Type: JIC Size

Cover Type: Opaque

Closure Type: 2-Screw

**Mounting Description:** Nonmetal flange fastened to back side brass inserts

**Box Features:** 

Installation Type:

Height: 13.85 in

Width: 12.07 in

**Depth:** 5.94 in

Usable Depth: 5.99 in

Volume: 1161 cu in

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

### **Application:**

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

#### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with: 1. EN / IEC 60204-1 and 60529 Type IP66 2. RoHS directive



**WARNING** – PROP 65 Click here for more information!