



## Product Info

**UPC:** 85339975410

**UNSPSC:** 39121302

**Carton Quantity:** 1

**Carton Weight:** 7 lbs

**Country of Origin:** United States of America

**Color:** Gray (RAL 7035)

**Material:** Polycarbonate frame and cover

**Additional Materials:** 316 stainless steel external hardware, Polyurethane (FIP) Formed-In-Place gasket system

## AMHMI164L

16"x14" HMI Cover Kit with hinged cover and stainless-steel snap latch

**Availability:**

**In-Stock** (Will ship within 2 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

**Cover Type:** Opaque

**Closure Type:** Metal Snap Latch

**Mounting Description:** 10 Screws

**Box Features:**

**Installation Type:**

**Height:** 15.87 in

**Width:** 14.07 in

**Depth:** 0.96 in

**Usable Depth:** 2.2 in

**Volume:** 491 cu in

### Features:

Non-corrosive, non-conductive, light weight with lower installation cost and longer life cycle cost compared to steel. Rigid design with a gasket system encased in a continuous channel on the cover and frame. Open back frame design with an opening size of 14.49" x 12.71" and is a UL recognized component for use with NEMA 4X enclosures. \*Will fit Allied Moulded enclosure sizes 18"x16" and larger.

### Application:

Cover and protect electrical and electronic controls including HMI (Human Machine Interface) instruments, touch pad controllers and pushbuttons mounted on the surface of NEMA 4X enclosures. No need to open the enclosure to view electronics or perform maintenance, decreasing arc flash risks and safety hazards.

### Standards:

Meets Requirements: ANSI/UL50, ANSI/UL50E, and ANSI/UL508A; [File No. E487574](#)

UL® listed and recognized component for use with CSA® listed enclosure products Types 1, 2, 3, 3R, 4, 4X, 12 and 13.

Complies With:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



 **WARNING** - PROP 65

[Click here for more information!](#)