



# **Product Info**

**Brand: POLYLINE® UPC:** 85339991212 **UNSPSC: 39121324** Carton Quantity: 1 Carton Weight: 9 lbs

Country of Origin: United States of America Color: Gray (RAL 7035) with clear cover Patents: U.S. Patent No. 7,572,975

Material: Polycarbonate box and clear polycarbonate cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

# AMP1648CCLF

16"x14"x8" POLYLINE® polycarbonate wall mount enclosure assembly with hinged clear cover and stainlesssteel snap latch

## Availability:

In-Stock (Will ship within 2 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

**Enclosure Type:** JIC Size

Cover Type: Clear Polycarbonate Closure Type: Metal Snap Latch

Mounting Description: Nonmetal flange fastened to

back side brass inserts

**Box Features: Installation Type:** Height: 15.98 in

Width: 13.98 in **Depth:** 7.81 in

Usable Depth: 8.27 in Volume: 1968 cu in

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

# **Application:**

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

## Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive







