



# **Product Info**

**Brand: ULTRALINE® UPC:** 85339959847 **UNSPSC: 39121324** Carton Quantity: 1 Carton Weight: 11 lbs

Country of Origin: United States of America Color: Gray (RAL 7035) with clear window Patents: U.S. Patent No. 7,572,975

Material: ULTRAGUARD® Fiberglass reinforced polyester compression molded SMC box and cover with bonded clear

polycarbonate window

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

## AMU1648WF

16"x14"x8" ULTRALINE® fiberglass wall mount enclosure assembly with 4-screw lift-off window cover

Availability:

Made to order; normally ships within 2 weeks after receipt of order - - Lead times may be delayed temporarily due to Covid-19 related events.

**Enclosure Type:** JIC Size

Cover Type: Opaque with Viewing Window

Closure Type: 4-Screw Lift-Off

Mounting Description: Nonmetal flange fastened to

back side brass inserts

**Box Features: Installation Type:** Height: 16.05 in Width: 14.27 in

Depth: 8 in

Usable Depth: 7.99 in Volume: 2061 cu in

### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system

encased in a continuous channel on the cover.

### **Application:**

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

### Complies with:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive









**■ WARNING** – PROP 65 Click here for more information!