



## AM1868RW

18"x16"x8" AM-R Series Fiberglass wall mount enclosure assembly with raised 4-screw lift-off window cover

**Availability:**

**Made to order;** normally ships within 2 weeks after receipt of order -- Lead times may be delayed temporarily due to Covid-19 related events.

**Enclosure Type:** JIC Size

**Cover Type:** Opaque with Viewing Window

**Closure Type:** 4-Screw Lift-Off

**Mounting Description:** Stainless steel feet fastened to back side brass inserts

**Box Features:**

**Installation Type:**

**Height:** 18.4 in

**Width:** 16.4 in

**Depth:** 8.01 in

**Usable Depth:** 9.11 in

**Volume:** 2453 cu in

## Product Info

**Brand:** AM-R Series

**UPC:** 85339919018

**UNSPSC:** 39121324

**Carton Quantity:** 1

**Carton Weight:** 18 lbs

**Country of Origin:** United States of America

**Color:** Gray (RAL 7035) with clear window

**Material:** ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and cover with bonded clear polycarbonate window

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

**Features:**

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

**Application:**

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

**Standards:**

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



**WARNING** - PROP 65

[Click here for more information!](#)