



## Product Info

**Brand:** Control Series

**UPC:** 85339924074

**UNSPSC:** 39121324

**Carton Quantity:** 1

**Carton Weight:** 24 lbs

**Country of Origin:** United States of America

**Color:** Gray (RAL 7035) with clear window

**Material:** ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and cover with bonded clear polycarbonate window

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

## AM24200RLW

24"x20"x10" Control Series fiberglass wall mount enclosure assembly with raised hinged window cover and stainless-steel snap latches

**Availability:**

**In-Stock** (Normally ships within 2-4 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

**Enclosure Type:** Wall Cabinets

**Cover Type:** Opaque with Viewing Window

**Closure Type:** Metal Snap Latch

**Mounting Description:** Stainless steel feet fastened to back side brass inserts

**Box Features:**

**Installation Type:**

**Height:** 24 in

**Width:** 20 in

**Depth:** 10 in

**Usable Depth:** 10.54 in

**Volume:** 5702 cu in

**Features:**

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

**Application:**

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

**Standards:**

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; [File No. E120175](#)

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



 **WARNING** - PROP 65

[Click here for more information!](#)