



## 9338-ES

3.5" dia. round fixture support (15 lbs.) box for use with nonmetallic sheathed cable

**Closure Type:**

**Mounting Description:** Snap bracket/metal ears wall compression

**Box Type:** Wall - Fixture Support

**Box Features:** Metal ears, Snap bracket

**Installation Type:** Old Work

**Width:** 3-1/2 in

**Depth:** 2 in

**Volume:** 14 cu in

**Fixture Rating:** 15lbs

## Product Info

**Brand:** fiberglassBOX

**UPC:** 85339460053

**UNSPSC:** 39121308

**Carton Quantity:** 50

**Carton Weight:** 20 lbs

**Country of Origin:** United States of America

**Color:** Off white

**Fire Classification: Fire Test of Building Construction Materials** ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C **Fire Resistance Classification in Wall Assemblies 2-Hours or less** Shall be separated by a horizontal distance of not less than 3 inches **Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less** Distance between boxes in adjacent cavities may be reduced to 5 ½ inches Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

**Material:** Fiberglass reinforced polyester

**Additional Materials:** Galvanized steel brackets and plated carbon steel fasteners, Polyvinyl chloride clamps

**Box Diameter:** 3.5

## Features:

Machine tapped fixture holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps bulk packed

## Application:

Old work residential construction 2 HR fire resistive walls (15 lbs fixture support)

**Box Diameter:** 3.5

## Standards:

ANSI / UL 514C: [File No. E30594](#)

