



## Product Info

**Brand:** fiberglassBOX

**UPC:** 85339411901

**UNSPSC:** 39121316

**Carton Quantity:** 50

**Carton Weight:** 26 lbs

**Country of Origin:** United States of America

**Color:** Off white

**Fire Classification: Fire Test of Building Construction Materials** ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C **Fire Resistance Classification in Wall Assemblies 2-Hours or less** Shall be separated by a horizontal distance of not less than 3 inches **Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less** Distance between boxes in adjacent cavities may be reduced to 5 ½ inches Note: *For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

**Material:** Fiberglass reinforced polyester

**Additional Materials:** Carbon steel fasteners, Plated carbon steel clamp and fasteners, Galvanized ground strap with plated carbon steel fastener and green plated carbon steel ground screw

**Box Diameter:** 3.5

## 9335-NGC2

3.5" dia. round fixture support box for use with nonmetallic sheathed cable

**Closure Type:**

**Mounting Description:** Nail-on with fether ring nails

**Box Type:** Ceiling - Fixture

**Box Features:** Nails, Grounding strap, Wire clamps

**Installation Type:** New Work

**Width:** 3.5 in

**Depth:** 2-15/16 in

**Volume:** 20.5 cu in

**Fixture Rating:** 50lbs

## Features:

Machine tapped fixture holes, ground strap, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

## Application:

New work residential construction 2 HR fire resistive walls and ceilings (50 lbs. fixture support)

**Box Diameter:** 3.5

**Standards:**

ANSI / UL 514C: [File No. E30594](#)

