



## PC213-16G

3.5" dia. round fixture support box for use with nonmetallic sheathed cable

**Closure Type:**

**Mounting Description:** Adjustable bar hanger - max 16" on center Joist application

**Box Type:** Ceiling - Fixture

**Box Features:** Bar hanger (16"), Grounding strap

**Installation Type:** New Work

**Width:** 3-1/2 in

**Depth:** 2-13/16 in

**Volume:** 21 cu in

**Fixture Rating:** 50lbs

## Product Info

**Brand:** flexBOX

**UPC:** 85339983057

**UNSPSC:** 39121316

**Carton Quantity:** 24

**Carton Weight:** 17 lbs

**Country of Origin:** United States of America

**Color:** Black

**Fire Classification: Fire Test of Building Construction Materials** ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) *Note: Products must also be certified to: ANSI / UL 514C Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less* Distance between boxes in adjacent cavities may be reduced to 5 ½ inches *Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

**Patents:** U.S. Patent No. 6,365,831 B1

**Material:** Polycarbonate

**Additional Materials:** Galvanized steel brackets and plated carbon steel fasteners, Galvanized ground strap with plated carbon steel fastener and green plated carbon steel ground screw

**Box Diameter:** 3.5

## Features:

Machine tapped fixture holes, ground strap

## Application:

New work residential construction 2 HR fire resistive walls and ceilings (50 lbs. fixture support)

**Box Diameter:** 3.5

## Standards:

ANSI / UL 514C: [File No. E30594](#)

