



PC213-BH

3.5" dia. round fixture support box for use with nonmetallic sheathed cable

Mounting Description: Adjustable bar hanger - 16" to 24" on center joist application

Box Type: Ceiling - Fixture

Box Features: Bar hanger

Installation Type: New Work

Width: 3-1/2 in

Depth: 2-13/16 in

Volume: 21 cu in

Fixture Rating: 50lbs

Product Info

Brand: flexBOX

UPC: 85339980308

UNSPSC: 39121316

Carton Quantity: 24

Carton Weight: 27 lbs

Country of Origin: United States of America

Color: Black

Fire Classification: Fire Test of Building Construction Materials ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) *Note: Products must also be certified to: ANSI / UL 514C Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less* Distance between boxes in adjacent cavities may be reduced to 5 ½ inches *Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

Patents: U.S. Patent No. 6,365,831 B1

Material: Polycarbonate

Additional Materials: Galvanized steel brackets and plated carbon steel fasteners

Box Diameter: 3.5

Features:

Machine tapped fixture holes

Application:

New work residential construction 2 HR fire resistive walls and ceilings (50 lbs. fixture support)

Box Diameter: 3.5

Standards:

ANSI / UL 514C: [File No. E30594](#)

