



PC213-BHG

3.5" dia. round fixture support box for use with nonmetallic sheathed cable

Carton Quantity: 24

Closure Type:

Mounting Description: Adjustable bar hanger - 16" to 24" on center joist application

Box Type: Ceiling - Fixture

Box Features: Bar hanger, Grounding strap

Installation Type: New Work

Width: 3-1/2 in

Depth: 2-13/16 in

Volume: 21 cu in

Fixture Rating: 50lbs

Product Info

Brand: flexBOX

UPC: 85339980315

UNSPSC: 39121316

Carton Weight: 27 lbs

Country of Origin: United States of America

Color: Black

Patents: U.S. Patent No. 6,365,831 B1

Material: Polycarbonate

Additional Materials: Galvanized steel brackets and plated carbon steel fasteners, Galvanized ground strap with plated carbon steel fastener and green plated carbon steel ground screw

Box Diameter: 3.5

Features:

Machine tapped fixture holes, ground strap

Application:

New work residential construction 2 HR fire resistive walls and ceilings (50 lbs. fixture support)

Box Diameter: 3.5

Standards:

ANSI / UL 514C: [File No. E30594](#)



Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)