



## **Product Info**

**Brand:** Control Series **UPC:** 8533998420 UNSPSC: 39121324 Carton Quantity: 1

Carton Weight: 31 lbs

Country of Origin: United States of America

Color: Gray (RAL 7035)

Material: ULTRAGUARD® Fiberglass reinforced polyester -

compression molded SMC box and Cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

# AM30248RQT

30"x24"x8" Control Series fiberglass wall mount enclosure assembly with raised hinged cover and stainless-steel quarter-turn latch

## Availability:

Made to order; normally ships within 2 weeks after receipt of order - - Lead times may be delayed temporarily due to Covid-19 related events.

**Enclosure Type:** Wall Cabinets

Cover Type: Opaque

Closure Type: Quarter Turn Latch

Mounting Description: Stainless steel feet fastened to

back side brass inserts

**Box Features: Installation Type:** Height: 30 in

Width: 24 in Depth: 8 in

Usable Depth: 8.65 in Volume: 7114 cu in

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

## **Application:**

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

#### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

### Complies with:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive









Click here for more information!