ALLIED MOULDED PRODUCTS, Inc.

419-636-4217
222 N. Union St.
Bryan, OH 43506

AMEC363012TW

36"x30"x12" Empire Series fiberglass wall mount enclosure assembly with hinged window cover and stainless-steel twist latch

Availability:
Made to order; normally ships within 2 weeks after receipt of order – – Lead times may be delayed temporarily due to Covid-19 related events.

Enclosure Type: Wall Cabinets

Cover Type: Opaque with Viewing Window

Closure Type: Metal Twist Latch

Mounting Description: Molded flange

Box Features:

Installation Type:

Height: 36.5 in

Width: 30.5 in

Depth: 12.03 in

Usable Depth: 12.48 in

Volume: 15062 cu in

Product Info

Brand: Empire Series

UPC: 85339972266

UNSPSC: 39121324

Carton Quantity: 1

Carton Weight: 77 lbs

Country of Origin: United States of America

Color: Gray (RAL 7035) with clear window

Material: ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and cover with bonded clear polycarbonate window

Additional Materials: Plated carbon steel internal hardware, 316 stainless steel external hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus molded-in mounting flanges and a formed-in-place polyurethane gasket system.

Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with:
1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive

WARNING – PROP 65
Click here for more information!