



**ALLIED
MOULDED
PRODUCTS, Inc.**

**419-636-4217
222 N. Union St.
Bryan, OH 43506**



SB-CB

4" dia. round adjustable fixture support box for use with nonmetallic sheathed cable

Mounting Description: 2 Screws

Box Type: Ceiling - Fixture

Box Features: Adjustable box (SLIDERBOX®), Screws

Installation Type: New Work, Old Work

Width: 4 in

Depth: 2-3/4 in

Volume: 25 cu in

Fixture Rating: 50lbs

Product Info

Brand: SLIDERBOX

UPC: 85339945055

UNSPSC: 39121316

Carton Quantity: 12

Carton Weight: 3 lbs

Country of Origin: United States of America

Color: Beige

Fire Classification: Fire Test of Building Construction Materials ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) *Note: Products must also be certified to: ANSI / UL 514C Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less* Distance between boxes in adjacent cavities may be reduced to 5 ½ inches *Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

Patents: U.S. Patent No. 7,855,338, U.S. Patent No. 6,365,831 B1

Material: Polycarbonate

Additional Materials: Carbon steel fasteners, Galvanized steel brackets and plated carbon steel fasteners

Box Diameter: 4

Features:

Machine tapped fixture holes, adjustable mounting plate for additional substrate thickness

Application:

New and old work residential construction 2 HR fire resistive floors and ceilings (50 lbs. fixture support)

Box Diameter: 4

Standards:

ANSI / UL 514C: [File No. E30594](#)

