



9350-FANV2B

4" dia. round fan support box for use with nonmetallic sheathed cable

Closure Type:

Mounting Description: Adjustable bar hanger - 16" to

24" on center joist application

Box Type: Ceiling - Fan/Fixture

Box Features: Bar hanger, Air-sealed flange (energy

efficient)

Installation Type: New Work

Width: 4 in
Depth: 2-7/16 in
Volume: 22.5 cu in
Fan Rating: 35lbs
Fixture Rating: 50lbs

Product Info

Brand: Vapor Seal UPC: 85339990239 UNSPSC: 39121316 Carton Quantity: 18 Carton Weight: 31 lbs

Country of Origin: United States of America

Color: Off white

Fire Classification: Fire Test of Building Construction Materials ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C Fire Resistance Classification in Wall Assemblies 2-Hours or less Shall be separated by a horizontal distance of not less than 3 inches Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less Distance between boxes in adjacent cavities may be reduced to 5 ½ inches Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

Patents: U.S. Patent No. 6,908,003 B2 **Material:** Fiberglass reinforced polyester

Additional Materials: Galvanized steel brackets and plated

carbon steel fasteners, Polyvinyl chloride clamps,

Polyurethane flange

Box Diameter: 4

Features:

Polyurethane flange for double drywall offset, machine tapped fixture holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed. New bar design – Replaces P/N 9350-FRBKBV2

Application:

New work residential construction 2 HR fire resistive walls and ceilings (35 lbs. fan support and 50 lbs. fixture support) – air-sealed electrical fan support box for Energy Star homes

Box Diameter: 4
Standards:

ANSI / UL 514C: File No. E30594



NEMA OS 4 – Energy Efficient Air-Sealed Boxes for Electrical Applications

