



9369-FBH

4" dia. round fan support box for use with nonmetallic sheathed cable

Closure Type:

Mounting Description: Back side mount with fasteners

Box Type: Ceiling - Fan/Fixture

Box Features: "HL" hanger

Installation Type: New Work

Width: 4 in

Depth: 1-3/4 in

Volume: 16 cu in

Fan Rating: 35lbs

Fixture Rating: 50lbs

Product Info

Brand: fiberglassBOX

UPC: 85339765011

UNSPSC: 39121316

Carton Quantity: 25

Carton Weight: 18 lbs

Country of Origin: United States of America

Color: Off white

Fire Classification: Fire Test of Building Construction Materials ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C **Fire Resistance Classification in Wall Assemblies 2-Hours or less** Shall be separated by a horizontal distance of not less than 3 inches **Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less** Distance between boxes in adjacent cavities may be reduced to 5 ½ inches Note: *For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

Material: Fiberglass reinforced polyester

Additional Materials: Galvanized steel brackets and plated carbon steel fasteners, Polyvinyl chloride clamps, Plated carbon steel fasteners

Box Diameter: 4

Features:

Fixture support bolts and nuts included, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

Application:

New work residential construction 2 HR fire resistive walls and ceilings (35 lbs. fan support and 50 lbs. fixture support)

Box Diameter: 4

Standards:

ANSI / UL 514C: [File No. E30594](#)

