



**ALLIED
MOULDED
PRODUCTS, Inc.**

**419-636-4217
222 N. Union St.
Bryan, OH 43506**



9370-FR

4" dia. round fan support box for use with nonmetallic sheathed cable

Mounting Description: Bottom mount

Box Type: Ceiling - Fan/Fixture

Installation Type: New Work, Old Work

Width: 4 in

Depth: 1-1/2 in

Volume: 8 cu in

Fan Rating: 70lbs

Fixture Rating: 110lbs

Product Info

Brand: fiberglassBOX

UPC: 85339766001

UNSPSC: 39121316

Carton Quantity: 24

Carton Weight: 6 lbs

Country of Origin: United States of America

Color: Off white

Fire Classification: **Fire Test of Building Construction Materials** ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C **Fire Resistance Classification in Wall Assemblies 2-Hours or less** Shall be separated by a horizontal distance of not less than 3 inches **Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less** Distance between boxes in adjacent cavities may be reduced to 5 ½ inches Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

Material: Fiberglass reinforced polyester

Additional Materials: Nonmetallic pop-in cable clamp, Plated carbon steel fasteners

Box Diameter: 4

Features:

1/2" deep base with side cube wiring capacity, fan/fixture screws for joist mounting

Application:

New and old work residential construction 2 HR fire resistive walls and ceilings (70 lbs. fan support and 110 lbs. fixture support)

Box Diameter: 4

Standards:

ANSI / UL 514C: [File No. E30594](#)

