



9350-BHKV2

4" dia. round fixture support box for use with nonmetallic sheathed cable

Closure Type:

Mounting Description: Adjustable bar hanger - 16" to

24" on center joist application

Box Type: Ceiling - Fixture

Box Features: Bar hanger, Speed "K" nonmetallic

clamps, Air-sealed flange (energy efficient)

Installation Type: New Work

Width: 4 in **Depth:** 2-7/16 in Volume: 22.5 cu in Fixture Rating: 50lbs

Product Info

Brand: Vapor Seal UPC: 85339104841 **UNSPSC: 39121316 Carton Quantity: 18** Carton Weight: 26 lbs

Country of Origin: United States of America

Color: Off white

Fire Classification: Fire Test of Building Construction Materials ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C Fire Resistance Classification in Wall Assemblies **2-Hours or less** Shall be separated by a horizontal distance of not less than 3 inches Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less Distance between boxes in adjacent cavities may be reduced to 5 ½ inches Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

Patents: U.S. Patent No. 6,908,003 B2 Material: Fiberglass reinforced polyester

Additional Materials: Galvanized steel brackets and plated

carbon steel fasteners, Polyvinyl chloride clamps,

Polyurethane flange **Box Diameter: 4**

Features:

Polyurethane flange for double drywall offset, machine tapped fixture holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

Application:

New work residential construction 2 HR fire resistive walls and ceilings (50 lbs. fixture support) - air-sealed electrical box for envelope walls and ceilings in Energy Star homes

Box Diameter: 4 Standards:

ANSI / UL 514C: File No. E30594



NEMA OS 4 - Energy Efficient Air-Sealed Boxes for **Electrical Applications**

