



## 9351-NGKV

4" dia. round fixture support box for use with nonmetallic sheathed cable

**Closure Type:** 

Mounting Description: Nail-on with fetter ring nails

Box Type: Ceiling - Fixture

**Box Features:** Nails, Grounding strap, Speed "K" nonmetallic clamps, Air-sealed flange (energy efficient)

**Installation Type:** New Work

Width: 4 in
Depth: 2-7/16 in
Volume: 22.5 cu in
Fixture Rating: 50lbs

## **Product Info**

Brand: Vapor Seal
UPC: 85339990932
UNSPSC: 39121316
Carton Quantity: 48
Carton Weight: 27 lbs

Country of Origin: United States of America

Color: Off white

Fire Classification: Fire Test of Building Construction Materials ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C Fire Resistance Classification in Wall Assemblies 2-Hours or less Shall be separated by a horizontal distance of not less than 3 inches Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less Distance between boxes in adjacent cavities may be reduced to 5 ½ inches Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

**Patents:** U.S. Patent No. 6,908,003 B2 **Material:** Fiberglass reinforced polyester

Additional Materials: Carbon steel fasteners, Polyvinyl

chloride clamps, Polyurethane flange

**Box Diameter:** 4

## Features:

Polyurethane flange for single drywall offset, machine tapped fixture holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed and ground strap

## **Application:**

New work residential construction 2 HR fire resistive walls and ceilings (50 lbs. fixture support) – air-sealed electrical outlet box for envelope walls and ceilings in Energy Star homes

**Box Diameter:** 4

Standards:

ANSI / UL 514C: File No. E30594



NEMA OS 4 – Energy Efficient Air-Sealed Boxes for Electrical Applications

