



ALLIED
MOULDED
PRODUCTS, Inc.

419-636-4217
222 N. Union St.
Bryan, OH 43506



9364-16K

4" dia. round fixture support box for use with nonmetallic sheathed cable *Replacement for 9364-16 and 9364-16C2*

Mounting Description: Adjustable bar hanger - max 16" on center Joist application

Box Type: Ceiling - Fixture

Box Features: Bar hanger (16"), Speed "K" nonmetallic clamps

Installation Type: New Work

Width: 4 in

Depth: 1-11/16 in

Volume: 15 cu in

Fixture Rating: 50lbs

Product Info

Brand: fiberglassBOX

UPC: 85339983026

UNSPSC: 39121316

Carton Quantity: 24

Carton Weight: 19 lbs

Country of Origin: United States of America

Color: Off white

Fire Classification: Fire Test of Building Construction Materials ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C **Fire Resistance Classification in Wall Assemblies 2-Hours or less** Shall be separated by a horizontal distance of not less than 3 inches **Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less** Distance between boxes in adjacent cavities may be reduced to 5 ½ inches Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

Material: Fiberglass reinforced polyester

Additional Materials: Galvanized steel brackets and plated carbon steel fasteners, Polyvinyl chloride clamps

Box Diameter: 4

Features:

Machine tapped fixture holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

Application:

New work residential construction 2 HR fire resistive walls and ceilings (50 lbs. fixture support)

Box Diameter: 4

Standards:

ANSI / UL 514C: [File No. E30594](#)

