



Product Info

Brand: Vapor Seal

UPC: 85339927051

UNSPSC: 39121316

Carton Weight: 10 lbs

Country of Origin: United States of America

Color: Off white

Patents: U.S. Patent No. 6,908,003 B2

Material: Fiberglass reinforced polyester

Additional Materials: Polyvinyl chloride clamps,
Polyurethane flange, Plated carbon steel fasteners

Box Diameter: 4

9371-FRV

4" dia. round fixture support box for use with nonmetallic sheathed cable

Carton Quantity: 24

Closure Type:

Mounting Description: Bottom mount

Box Type: Ceiling - Fan/Fixture

Box Features: Air-sealed flange (energy efficient)

Installation Type: New Work

Width: 4 in

Depth: 2-7/8 in

Volume: 12 cu in

Fan Rating: 70lbs

Fixture Rating: 110lbs

Features:

Polyurethane flange for single drywall offset, 1/2" deep base with side cube wiring capacity, fan/fixture screws for joist mounting, machine tapped fixture holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

Application:

New work residential construction 2 HR fire resistive walls and ceilings (70 lbs. fan support and 110 lbs. fixture support), air-sealed electrical fan support box for Energy Star homes

Box Diameter: 4

Standards:

ANSI / UL 514C: [File No. E30594](#)



NEMA OS 4 - Energy Efficient Air-Sealed Boxes for Electrical Applications



Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)
