



**ALLIED
MOULDED
PRODUCTS, Inc.**

**419-636-4217
222 N. Union St.
Bryan, OH 43506**



AC9500BULK

4" dia. round fixture support box with 7" square mounting flange for use with nonmetallic sheathed cable

Closure Type:

Mounting Description: Back side mount with fasteners

Box Features:

Installation Type: New Work

Width: 4 in

Depth: 1-1/4 in

Volume: 12 cu in

Fixture Rating: 15lbs

Product Info

UPC: 85339095033

UNSPSC: 39121309

Carton Quantity: 50

Carton Weight: 29 lbs

Country of Origin: United States of America

Color: Beige

Fire Classification: Fire Test of Building Construction Materials ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less Shall be separated by a horizontal distance of not less than 24 inches **Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less** Distance between boxes must be 4-½ feet from one another *Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

Material: Fiberglass reinforced polyester

Additional Materials: Nonmetallic pop-in cable clamp

Box Diameter: 4

Features:

Machine tapped fixture holes, "pop-in" cable clamp, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

Application:

Residential home - exterior light fixture electrical box (15 lb fixture rating) for use with nonmetallic sheathed cable

Box Diameter: 4

Standards:

ANSI / UL 514C: [File No. E30594](#)

