



## 9339-Z+1

4 square inch electrical junction box for use with nonmetallic sheathed cable

**Closure Type:**

**Mounting Description:** Stud mount "Z" hanger bracket offset for flush mount plaster ring

**Box Type:** Wall - Junction

**Box Features:** "Z" hanger(s)

**Installation Type:** New Work

**Height:** 4-1/4 in

**Width:** 4-1/4 in

**Depth:** 1-1/4 in

**Volume:** 16 cu in

## Product Info

**Brand:** fiberglassBOX

**UPC:** 85339103141

**UNSPSC:** 39121332

**Carton Quantity:** 50

**Carton Weight:** 22 lbs

**Country of Origin:** United States of America

**Color:** Off white

**Fire Classification: Fire Test of Building Construction Materials** ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) *Note: Products must also be certified to: ANSI / UL 514C Fire Resistance Classification in Wall Assemblies* **2-Hours or less** Shall be separated by a horizontal distance of not less than 3 inches *Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

**Material:** Fiberglass reinforced polyester

**Additional Materials:** Galvanized steel brackets and plated carbon steel fasteners, Plated carbon steel clamp and fasteners, Carbon steel fasteners

## Features:

Machine tapped cover screw holes, cover screws included, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, C2 clamps bulk packed

## Application:

In the wall junction box with optional single and two gang plaster ring covers for junction box capacity and device applications - 2 HR fire resistive walls

## Standards:

ANSI / UL 514C: [File No. E30594](#)

