

419-636-4217 222 N. Union St. Bryan, OH 43506



9342-C2

4 square inch electrical junction box for use with nonmetallic sheathed cable Closure Type: Mounting Description: Bottom mount Box Type: Wall - Junction Box Features: Wire clamps Installation Type: New Work Height: 4 in Width: 4 in Depth: 2-1/4 in Volume: 27.3 cu in

Product Info

Brand: fiberglassBOX

UPC: 85339103462 **UNSPSC:** 39121332

Carton Quantity: 50

Carton Weight: 25 lbs

Country of Origin: United States of America

Color: Off white

Fire Classification: Fire Test of Building Construction Materials ANSI / UL 263: <u>File No. CEYY.R9379</u> (Category / File No.) *Note: Products must also be certified to: ANSI / UL 514C* **Fire Resistance Classification in Wall Assemblies 2-Hours or less** Shall be separated by a horizontal distance of not less than 3 inches *Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

Material: Fiberglass reinforced polyester

Additional Materials: Plated carbon steel clamp and fasteners, Carbon steel fasteners

Features:

Machine tapped cover screw holes, cover screws included, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

Application:

In the wall junction box with optional single and two gang plaster ring covers for junction box capacity and device applications – 2 HR fire resistive walls

Standards:

ANSI / UL 514C: File No. E30594

×