



## **Product Info**

Brand: fiberglassBOX

**UPC:** 85339103424 **UNSPSC:** 39121332

Carton Quantity: 50

Carton Weight: 32 lbs

Country of Origin: United States of America

Color: Off white

**Fire Classification: Fire Test of Building Construction Materials** ANSI / UL 263: File No. CEYY.R9379 (Category / File No.) *Note: Products must also be certified to: ANSI / UL 514C* **Fire Resistance Classification in Wall Assemblies 2-Hours or less** Shall be separated by a horizontal distance of not less than 3 inches *Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)* 

Material: Fiberglass reinforced polyester

**Additional Materials:** Galvanized steel brackets and plated carbon steel fasteners, Plated carbon steel clamp and fasteners, Carbon steel fasteners

# 9342-HN

4 square inch electrical junction box for use with nonmetallic sheathed cable Closure Type: Mounting Description: Nail-on backside HN hanger bracket for adjusting to additional wall/ceiling substrate Box Type: Wall - Junction Box Features: "HN" bracket Installation Type: New Work Height: 4 in Width: 4 in Depth: 2-1/4 in

Volume: 27.3 cu in

#### Features:

Machine tapped cover screw holes, cover screws included, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, C2 wire clamps bulk packed

## **Application:**

In the wall junction box with optional single and two gang plaster ring covers for junction box capacity and device applications – 2 HR fire resistive walls

## Standards:

ANSI / UL 514C: File No. E30594

×