



Product Info

Brand: fiberglassBOX

UPC: 85339103745

UNSPSC: 39121332

Carton Weight: 27 lbs

Country of Origin: United States of America

Color: Off white

Material: Fiberglass reinforced polyester

Additional Materials: Carbon steel fasteners, Polyvinyl chloride clamps

9343-NK

4 square inch electrical junction box for use with nonmetallic sheathed cable *Replacement for 9343-N*

Carton Quantity: 50

Mounting Description: Angled mid nails

Box Type: Wall - Junction

Box Features: Nails, Speed "K" nonmetallic clamps

Installation Type: New Work

Height: 4-1/16 in

Width: 4-1/16 in

Depth: 2-1/2 in

Volume: 32.3 cu in

Features:

Machine tapped cover screw holes, cover screws included, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

Application:

In the wall junction box with optional single and two gang plaster ring covers for junction box capacity and device applications - 2 HR fire resistive walls

Standards:

ANSI / UL 514C: [File No. E30594](#)



LISTED

Fire Classification:

Fire Test of Building Construction Materials

ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)