



Product Info

Brand: fiberglassBOX

UPC: 85339103769

UNSPSC: 39121332

Carton Quantity: 50

Carton Weight: 27 lbs

Country of Origin: United States of America

Color: Off white

Fire Classification: Fire Test of Building Construction Materials ANSI / UL 263: [File No. CEYY.R9379](#) (Category / File No.) *Note: Products must also be certified to: ANSI / UL 514C Fire Resistance Classification in Wall Assemblies*
2-Hours or less Shall be separated by a horizontal distance of not less than 3 inches *Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

Material: Fiberglass reinforced polyester

Additional Materials: Carbon steel fasteners, Polyvinyl chloride clamps, Carbon steel fasteners

9343-SSK

4 square inch electrical junction box for use with nonmetallic sheathed cable

Closure Type:

Mounting Description: Steel stud screws for use with non-load bearing studs 22 gauge or lighter

Box Type: Wall - Junction

Box Features: Screws, Speed "K" nonmetallic clamps

Installation Type: New Work

Height: 4-1/16 in

Width: 4-1/16 in

Depth: 2-1/2 in

Volume: 32.3 cu in

Features:

Machine tapped cover screw holes, cover screws included, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

Application:

In the wall junction box with optional single and two gang plaster ring covers for junction box capacity and device applications - 2 HR fire resistive walls

Standards:

ANSI / UL 514C: [File No. E30594](#)

