



Product Info

Brand: Control XL Series

UPC: 8533999804

UNSPSC: 39121324

Carton Quantity: 1

Carton Weight: 77 lbs

Country of Origin: India

Color: Gray (RAL 7035)

Material: ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and Cover

Additional Materials: Plated carbon steel internal hardware, 316 stainless steel external hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

AMXL403212L3PT

40x32x12 Control XL Series fiberglass wall mount enclosure assembly with hinged cover and stainless-steel 3-point latching handle

Availability:

In-Stock (Will ship within 2 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

Enclosure Type: Wall Cabinets

Cover Type: Opaque

Closure Type: 3-Point Handle

Mounting Description: Stainless steel feet fastened to back side brass inserts

Box Features:

Installation Type:

Height: 39.73 in

Width: 31.23 in

Depth: 11.5 in

Usable Depth: 11.41 in

Volume: 14269 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus molded-in mounting flanges and a formed-in-place polyurethane gasket system.

Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; [File No. E120175](#)

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



WARNING - PROP 65

[Click here for more information!](#)