



## Product Info

**Brand:** POLYLINE®

**UPC:** 85339934691

**UNSPSC:** 39121324

**Carton Quantity:** 1

**Carton Weight:** 2 lbs

**Country of Origin:** United States of America

**Color:** Gray (RAL 7035)

**Patents:** U.S. Patent No. 7,572,975

**Material:** Polycarbonate box and cover

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), Polycarbonate mounting brackets, Plated carbon steel internal hardware, Polyurethane (FIP) Formed-In-Place gasket system

## AMP443L

4"x4"x3" POLYLINE® polycarbonate wall mount enclosure assembly with hinged cover and stainless-steel snap latch

**Availability:**

**In-Stock** (Normally ships within 2-4 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

**Enclosure Type:** JIC Size

**Cover Type:** Opaque

**Closure Type:** Metal Snap Latch

**Mounting Description:** Nonmetal feet fastened with self-threading screws

**Box Features:**

**Installation Type:**

**Height:** 4.09 in

**Width:** 4.09 in

**Depth:** 3.88 in

**Usable Depth:** 3.07 in

**Volume:** 51.75 cu in

**Features:**

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

**Application:**

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

**Standards:**

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; [File No. E120175](#)

CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



 **WARNING** - PROP 65

[Click here for more information!](#)