



## Product Info

**Brand:** Empire Series

**UPC:** 85339940098

**UNSPSC:** 39121324

**Carton Quantity:** 1

**Carton Weight:** 430 lbs

**Country of Origin:** India

**Color:** Gray (RAL 7035)

**Material:** ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and Cover

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), Plated carbon steel internal hardware, EPDM Spring loaded gasket, 316 stainless steel external 3-point latching handle, 316 stainless steel lifting eye bolts, Plated alloy steel bonding fastener

## AM724925FSDD

72"x49"x25" Empire Series fiberglass free standing double-door enclosure with hinged cover and stainless-steel 3-point latching handles

**Availability:**

**In-Stock** (Normally ships within 2-4 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

**Enclosure Type:** Free Standing

**Cover Type:** Opaque

**Closure Type:** 4-Screw Lift-Off

**Mounting Description:** Free standing on floor

**Box Features:**

**Installation Type:**

**Height:** 72 in

**Width:** 49 in

**Depth:** 24.5 in

**Usable Depth:** 24.35 in

**Volume:** 90599 cu in

### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus a spring loaded gasket system.

### Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 4, and 4X; [File No. E120175](#)

CSA C22.2 No. 94 Types 1, 4, and 4X; File No. 89590

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



 **WARNING** - PROP 65

[Click here for more information!](#)