



AM1648IW

AM Series fiberglass wall mount enclosure assembly with

4-screw lift-off window cover **Enclosure Type:** IIC Size

Cover Type: Opaque with Viewing Window

Closure Type: 4-screw lift-off

Mounting Description: Stainless steel feet fastened to

back side brass inserts

Box Features:

Installation Type:

Height: 413 mm Width: 366 mm

Depth: 207 mm Usable Depth: 195 mm

Volume: 1905 cu mm

Product Info

Brand: AM Series **UPC:** c8b7b2fe05d8 **Carton Quantity: 1** Carton Weight: 3.538 kg Country of Origin: India

Color: Gray (RAL 7035) with clear window

Material: Fiberglass Reinforced Polyester - compression

molded SMC box and cover

Additional Materials: 304 stainless steel external hardware (hinges/latches/fasteners), 304 Stainless Steel Mounting brackets, 304 Stainless Steel internal hardware,

Brass inserts, Neoprene gasket

Features:

Non-corrosive, non-conductive, UV protected, Flameretardent, Impact resistant, Chemical Resistant, Leight Weight with lower installation cost, Negligible maintenance cost, easy to modify and Loger life cycle compare to Steel/Polycarbonate. Rigid design with Back panel inserts plus Stainless Steel wall mounting brackets and neoprene gasket encased in a continous channel on the cover.

Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

IEC-62208, IEC-60695-2-11:2000, IEC-60529:2013-08, IEC-60068-2-2:2007, IEC-62262-2002, UL-94 5VA, CE, RoHS Compliant and Reach Compliant.







