





## **AM1426ILW**

AM Series fiberglass wall mount enclosure assembly with hinged window cover and stainless-steel snap latch **Enclosure Type:** IIC Size

Cover Type: Opaque with Viewing Window

**Mounting Description:** Stainless steel feet fastened to back side brass inserts

Height: 359 mm

Width: 311 mm

Depth: 156 mm

Usable Depth: 144 mm

Volume: 1062 cu mm

# **Product Info**

Brand: AM Series

UPC: 7b9e81bc5058

**Carton Quantity:** 1

Carton Weight: 2.109 kg

Country of Origin: India

Color: Gray (RAL 7035) with clear window

**Material:** Fiberglass Reinforced Polyester - compression molded SMC box and cover

Additional Materials: 304 Stainless Steel Mounting brackets, 304 Stainless Steel internal hardware, 304 stainless steel external hardware (hinges/latches/fasteners), Brass inserts

#### Features:

Non-corrosive, non- conductive, UV protected, Flameretardent, Impact resistant, Chemical Resistant, Leight Weight with lower installation cost, Negligible maintenance cost, easy to modify and Loger life cycle compare to Steel/Polycarbonate. Rigid design with Back panel inserts plus Stainless Steel wall mounting brackets and neoprene gasket encased in a continous channel on the cover.

### Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

## Standards:

IEC-62208, IEC-60695-2-11:2000, IEC-60529:2013-08, IEC-60068-2-2:2007, IEC-62262-2002, UL-94 5VA, CE, RoHS Compliant and Reach Compliant.

