





Product Info

Brand: AM Series
UPC: AM1084IH
Carton Quantity: 1
Carton Weight: 2.7 kg
Country of Origin: India
Color: RAL 7035
UV Rating: 5000 Hours
IP Rating: IP66
IK Rating: IK08
Fire Classification: Glow Wire at 960°C
Flame Resistance: 5VA

Material: Fiberglass Reinforced Polyester - compression molded SMC box and cover

Additional Materials: 304 Stainless Steel Mounting brackets|304 Stainless Steel internal hardware|304 stainless steel external hardware (hinges/latches/fasteners)|Brass inserts

AM1084IH

AM-JIC Series fibreglass wall mount enclosure assembly with Top cover 2 Screw down & One Side Hinge. External Hardware are of SS 304 Series. IP Rating - IP 66

Enclosure Type: JIC Size Cover Type: Opaque

Closure Type: 2-Screw

Mounting Description: SS 304 feet fastened to back side brass inserts

Box Features:

Installation Type: Wall Mount Height: 258 mm Width: 210 mm

Depth: 105 mm

Usable Depth: 93 mm

Features:

Non-corrosive, non- conductive, UV protected, Flameretardent, Impact resistant, Chemical Resistant, Leight Weight with lower installation cost, Negligible maintenance cost, easy to modify and Loger life cycle compare to Steel/Polycarbonate. Rigid design with Back panel inserts plus Stainless Steel wall mounting brackets and neoprene gasket encased in a continous channel on the cover.

Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

IEC-62208, IEC-60695-2-11:2000, IEC-60529:2013-08, IEC-60068-2-2:2007, IEC-62262-2002, UL-94 5VA, CE, RoHS Compliant and Reach Compliant.

