



Product Info

Brand: AM Series

UPC: AM864IL

Carton Quantity: 1

Carton Weight: 1.9 kg

Country of Origin: India

Color: RAL 7035

UV Rating: 5000 Hours

IP Rating: IP66

IK Rating: IK08

Fire Classification: Glow Wire at 960°C

Flame Resistance: 5VA

Material: Fiberglass Reinforced Polyester - compression molded SMC box and cover

Additional Materials: 304 Stainless Steel Mounting brackets|304 Stainless Steel internal hardware|304 stainless steel external hardware (hinges/latches/fasteners)|Brass inserts

AM864IL

AM-JIC Series fibreglass wall mount enclosure assembly with Snap Latch Locking System & One Side Hinge. External Hardware are of SS 304 Series. IP Rating - IP 66

Enclosure Type: JIC Size

Cover Type: Opaque

Closure Type: SS 304 Snap Latch

Mounting Description: SS 304 feet fastened to back side brass inserts

Box Features:

Installation Type: Wall Mount

Height: 203 mm

Width: 156 mm

Depth: 105 mm

Usable Depth: 93 mm

Features:

Non-corrosive, non- conductive, UV protected, Flameretardent, Impact resistant, Chemical Resistant, Leight Weight with lower installation cost, Negligible maintenance cost, easy to modify and Loger life cycle compare to Steel/Polycarbonate. Rigid design with Back panel inserts plus Stainless Steel wall mounting brackets and neoprene gasket encased in a continous channel on the cover.

Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

IEC 60529: Ingress Protection - IP66

IEC-62262: Impact Resistance - IK08

ASTM G154: UV - 5000Hrs

UL94: Flammability Rating - 5VA

IEC 62208: Thermal stability - 70°C, 168hrs

IEC 60695: Glow Wire Test - 960°C

CE, RoHS and Reach Complaint

