



## Product Info

**Brand:** ULTRAPLUG®

**UPC:** 0.5

**UPC:** AMHS125I

**UNSPSC:** 39121321

**Carton Quantity:** 1

**Carton Weight:** 0.026 kg

**Country of Origin:** United States of America

**Color:** Gray (RAL 7035)

**Patents:** U.S. Patent No. 9,045,932

**Material:** Polycarbonate

**Additional Materials:** Blended neoprene/EPDM gasket

## AMHS125I

AMHS125 - ULTRAPLUG® enclosure hole plug  
(1.687-1.875) - Light Gray

### Availability:

**In-Stock** (Will ship within 2 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

**Trade Size Ref:** 1-1/4" Conduit (1.734)

**Plugged Hole Dia. Range:** 1.687-1.875

**Plug Diameter:** 2.183

**Plug Head Height:** 0.235

**Nut Height:** 0.5

### Features:

Plug fins are self centering, anti-rotational design for fast and easy one person assembly and no-tools tightening

### Application:

Capable of plugging unused holes in NEMA 4X enclosures and designed to maintain applicable NEMA/UL/CSA enclosure ratings

### Standards:

Meets Requirements: ANSI/UL50, ANSI/UL50E, and ANSI/UL508A; [File No. E487574](#)

UL® listed and recognized component for use with CSA® listed enclosure products Types 1, 3, 3R, 4, 4X, and 12.

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



 **WARNING** - PROP 65

[Click here for more information!](#)