



Product Info

Brand: ULTRAPLUG®

UPC: 0.75

UPC: AMHS2001

Carton Quantity: 1

Carton Weight: 0.056 kg

Country of Origin: United States of America

Color: RAL 7035

UV Rating: 5000 Hours

IP Rating: IP66

IK Rating: IK08

Fire Classification: Glow Wire at 960°C

Flame Resistance: 5VA

Patents: U.S. Patent No. 9,045,932

Material: Polycarbonate

Additional Materials: Blended neoprene/EPDM gasket

AMHS2001

AMHS200 - ULTRAPLUG® enclosure hole plug
(2.500-2.750) - Light Gray

Availability:

In-Stock (Will ship within 2 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

Trade Size Ref: 2" Conduit (2.469)

Plugged Hole Dia. Range: 2.500-2.75

Plug Diameter: 3.12

Plug Head Height: 0.235

Nut Height: 0.75

Features:

Plug fins are self centering, anti-rotational design for fast and easy one person assembly and no-tools tightening

Application:

Capable of plugging unused holes in NEMA 4X enclosures and designed to maintain applicable NEMA/UL/CSA enclosure ratings

Standards:

IEC 60529: Ingress Protection - IP66

CE, RoHS and Reach Complaint

