



## AMHS200I

AMHS200 - ULTRAPLUG® enclosure hole plug  
(2.500-2.750) - Light Gray

### Availability:

**In-Stock** (Will ship within 2 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

**Trade Size Ref:** 2" Conduit (2.469)

**Plugged Hole Dia. Range:** 2.500-2.75

**Plug Diameter:** 3.12

**Plug Head Height:** 0.235

**Nut Height:** 0.75

## Product Info

**Brand:** ULTRAPLUG®

**UPC:** 0.75

**UPC:** AMHS200I

**Carton Quantity:** 1

**Carton Weight:** 0.056 kg

**Country of Origin:** United States of America

**Color:** RAL 7035

**UV Rating:** 5000 Hours

**IP Rating:** IP66

**IK Rating:** IK08

**Fire Classification:** Glow Wire at 960°C

**Flame Resistance:** 5VA

**Patents:** U.S. Patent No. 9,045,932

**Material:** Polycarbonate

**Additional Materials:** Blended neoprene/EPDM gasket

### Features:

Plug fins are self centering, anti-rotational design for fast and easy one person assembly and no-tools tightening

### Application:

Capable of plugging unused holes in NEMA 4X enclosures and designed to maintain applicable NEMA/UL/CSA enclosure ratings

### Standards:

IEC 60529: Ingress Protection - IP66

CE, RoHS and Reach Compliant

