





# **Product Info**

Brand: ULTRAPLUG® UPC: 0.75 UPC: AMHS200I Carton Quantity: 1 Carton Weight: 0.056 kg Country of Origin: United States of America Color: RAL 7035 UV Rating: 5000 Hours IP Rating: IP66 IK Rating: IK08 Fire Classification: Glow Wire at 960∘C Flame Resistance: 5VA Patents: U.S. Patent No. 9,045,932 Material: Polycarbonate Additional Materials: Blended neoprene/EPDM gasket

## AMHS200I

AMHS200 - ULTRAPLUG® enclosure hole plug (2.500-2.750) - Light Gray Availability: In-Stock (Will ship within 2 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

Trade Size Ref: 2" Conduit (2.469)
Plugged Hole Dia. Range: 2.500-2.75

Plug Diameter: 3.12

Plug Head Height: 0.235

Nut Height: 0.75

### Features:

Plug fins are self centering, anti-rotational design for fast and easy one person assembly and no-tools tightening

### Application:

Capable of plugging unused holes in NEMA 4X enclosures and designed to maintain applicable NEMA/UL/CSA enclosure ratings

### Standards:

IEC 60529: Ingress Protection – IP66 CE, RoHS and Reach Complaint

