



Product Info

Brand: ULTRAPLUG®

UPC: 0.75

UPC: AMHS250I

UNSPSC: 39121321

Carton Quantity: 1

Carton Weight: 0.067 kg

Country of Origin: United States of America

Color: RAL 7035

Patents: U.S. Patent No. 9,045,932

Material: Polycarbonate

Additional Materials: Blended neoprene/EPDM gasket

AMHS250I

AMHS250 - ULTRAPLUG® enclosure hole plug
(2.875-3.125) - Light Gray

Availability:

In-Stock (Normally ships within 2-4 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

Trade Size Ref: 2-1/2" Conduit (2.969)

Plugged Hole Dia. Range: 2.875-3.125

Plug Diameter: 3.495

Plug Head Height: 0.235

Nut Height: 0.75

Features:

Plug fins are self centering, anti-rotational design for fast and easy one person assembly and no-tools tightening

Application:

Capable of plugging unused holes in NEMA 4X enclosures and designed to maintain applicable NEMA/UL/CSA enclosure ratings

Standards:

Meets Requirements: ANSI/UL50, ANSI/UL50E, and ANSI/UL508A; [File No. E487574](#)

UL® listed and recognized component for use with CSA® listed enclosure products Types 1, 3, 3R, 4, 4X, and 12.

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



 **WARNING** - PROP 65

[Click here for more information!](#)