



Product Info

Brand: POLYLINE®
UPC: 85339985211

UNSPSC: 39121324

Carton Quantity: 1

Carton Weight: 6 lbs

Country of Origin: United States of America

Color: Gray (RAL 7035) with clear cover

Patents: U.S. Patent No. 7,572,975

Material: Polycarbonate box and clear polycarbonate cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners), Brass inserts, Plated carbon steel internal hardware, Polycarbonate mounting brackets, Polyurethane (FIP) Formed-In-Place gasket system

AMP1226CCHF

12"x12"x6" POLYLINE® polycarbonate wall mount enclosure assembly with 2-screw hinged clear cover **Availability:** In-Stock (Will ship within 2 business days after receipt of

order) – Lead times may be delayed temporarily due to Covid-19 related events.

Enclosure Type: JIC Size

Cover Type: Clear Polycarbonate

Closure Type: 2-Screw

Mounting Description: Nonmetal flange fastened to back side brass inserts

Height: 11.93 in

Width: 11.93 in

Depth: 5.94 in

Usable Depth: 6.06 in

Volume: 864 cu in

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; $\underline{\rm File}$ No. $\underline{\rm E120175}$

CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with: 1. EN / IEC 60204-1 and 60529 Type IP66 2. RoHS directive



WARNING – PROP 65 Click here for more information!