




Product Info

Brand: POLYLINE®

UPC: AMP664IHF

UNSPSC: 39121324

Carton Quantity: 1

Carton Weight: 0.907 kg

Country of Origin: United States of America

Color: RAL 7035

Patents: U.S. Patent No. 7,572,975

Material: Polycarbonate box and cover

AMP664IHF

AMP664HF - 6"x6"x4" POLYLINE® polycarbonate wall mount enclosure assembly with 2-screw hinged cover

Availability:

In-Stock (Normally ships within 2-4 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

Enclosure Type: JIC Size

Cover Type: Opaque

Closure Type: 2-Screw

Mounting Description: Nonmetal flange fastened to back side brass inserts

Height: 6.03 mm

Width: 6.26 mm

Depth: 3.94 mm

Usable Depth: 4.06 mm

Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; [File No. E120175](#)

CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive

