



## AMP864I

AMP864 - 8"x6"x4" POLYLINE® polycarbonate wall mount enclosure assembly with 4-screw lift-off cover

### Availability:

**In-Stock** (Will ship within 2 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

**Enclosure Type:** JIC Size

**Cover Type:** Opaque

**Closure Type:** 4-Screw Lift-Off

**Mounting Description:** Nonmetal feet fastened to back side brass inserts

**Height:** 7.94 mm

**Width:** 6.16 mm

**Depth:** 3.98 mm

**Usable Depth:** 4.18 mm

**Volume:** 237 cu mm

## Product Info

**Brand:** POLYLINE®

**UNSPSC:** 39121324

**Carton Quantity:** 1

**Carton Weight:** 0.907 kg

**Country of Origin:** United States of America

**Color:** Gray (RAL 7035)

**Patents:** U.S. Patent No. 7,572,975

**Material:** Polycarbonate box and cover

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), Brass inserts, Plated carbon steel internal hardware, Polycarbonate mounting brackets, Polyurethane (FIP) Formed-In-Place gasket system

### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

### Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 6P, 12 and 13; [File No. E120175](#)

CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 6P, 12 and 13; File No. 89590

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66 and units rated 6P are IP68 (submersible up to 24 hours at a depth of 6 feet/1.8 meters)
2. RoHS directive



**⚠ WARNING - PROP 65**  
[Click here for more information!](#)