



# **Product Info**

**Brand:** POLYLINE® **UPC:** AMP864IHF **UNSPSC: 39121324 Carton Quantity:** 1 Carton Weight: 0.907 kg

Country of Origin: United States of America

Color: RAL 7035

Patents: U.S. Patent No. 7.572.975 Material: Polycarbonate box and cover

Additional Materials: 316 stainless steel external hardware (hinges/latches/fasteners)|Brass inserts|Plated carbon steel internal hardware|Polycarbonate mounting brackets|Polyurethane (FIP) Formed-In-Place gasket system

# AMP864IHF

AMP864HF - 8"x6"x4" POLYLINE® polycarbonate wall mount enclosure assembly with 2-screw hinged cover

Availability:

In-Stock (Will ship within 2 business days after receipt of order) - Lead times may be delayed temporarily due to Covid-19 related events.

**Enclosure Type:** JIC Size Cover Type: Opaque Closure Type: 2-Screw

Mounting Description: Nonmetal flange fastened to

back side brass inserts

**Box Features:** 

Installation Type: Wall Mount

Height: 7.94 mm Width: 6.16 mm **Depth:** 3.98 mm Usable Depth: 4.18 mm

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

### **Application:**

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

## Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive







