+91.80.67926666
NO.199 & 242, Road No. 8
Bommasandra, Jigani Link Road
Bangalore, Karnataka

# AM24240IRL

Control Series Fibre Reinforced Polyester (FRP) enclosure with stainless Steel 300-Series hinge & snap latch with Raised cover.

**Enclosure Type:** Wall Cabinets

**Cover Type:** Opaque

**Closure Type:** metal snap latch

**Mounting Description:** Stainless steel feet fastened to back side brass inserts

**Box Features:**

**Installation Type:**

**Height:** 610 mm

**Width:** 610 mm

**Depth:** 257 mm

**Usable Depth:** 268 mm

**Volume:** 6843 cu mm

## Product Info

**Brand:** Control Series

**UPC:** 972e9cebf9ad

**Carton Quantity:** 1

**Carton Weight:** 5.488 kg

**Country of Origin:** India

**Color:** Gray (RAL 7035)

**Material:** Fiberglass Reinforced Polyester - compression molded SMC box and cover

**Additional Materials:** 304 stainless steel external hardware (hinges/latches/fasteners), 304 Stainless Steel Mounting brackets, 304 Stainless Steel internal hardware, Brass inserts, Neoprene gasket

**Features:**

Non-corrosive, non- conductive, UV protected, Flameretardent, Impact resistant, Chemical Resistant, Leight Weight with lower installation cost, Negligible maintenance cost, easy to modify and Loger life cycle compare to Steel/Polycarbonate. Rigid design with Back panel inserts plus Stainless Steel wall mounting brackets and neoprene gasket encased in a continous channel on the cover.

**Application:**

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

**Standards:**

- IEC 60529: Ingress Protection – IP66
- IEC-62262: Impact Resistance – IK08
- ASTM G154: UV – 5000Hrs
- UL94: Flammability Rating – 5VA
- IEC 62208: Thermal stability – 70°C, 168hrs
- IEC 60695: Glow Wire Test – 960°C
- CE, RoHS and Reach Complaint