



# **Product Info**

Brand: Control Series

UPC: bd0e6e07c738

Carton Quantity: 1

Carton Weight: 5.058 kg

Country of Origin: India

Color: Gray (RAL 7035) with clear window

**Material:** Fiberglass Reinforced Polyester - compression molded SMC box and cover

Additional Materials: 304 stainless steel external hardware (hinges/latches/fasteners), 304 Stainless Steel Mounting brackets, 304 Stainless Steel internal hardware, Brass inserts, Neoprene gasket

## AM24200IRLSW

Control Series Fibre Reinforced Polyester (FRP) enclosure with stainless Steel 300-Series short hinge & snap latch with transparent window & Raised cover.

Enclosure Type: Wall Cabinets

### **Closure Type:**

**Mounting Description:** Stainless steel feet fastened to back side brass inserts

| Box Features:        |  |
|----------------------|--|
| Installation Type:   |  |
| Height: 610 mm       |  |
| Width: 508 mm        |  |
| <b>Depth:</b> 257 mm |  |
| Usable Depth: 268 mm |  |
| Volume: 5702 cu mm   |  |
|                      |  |

#### Features:

Non-corrosive, non- conductive, UV protected, Flameretardent, Impact resistant, Chemical Resistant, Leight Weight with lower installation cost, Negligible maintenance cost, easy to modify and Loger life cycle compare to Steel/Polycarbonate. Rigid design with Back panel inserts plus Stainless Steel wall mounting brackets and neoprene gasket encased in a continous channel on the cover.

#### Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

#### Standards:

IEC 60529: Ingress Protection - IP66

IEC-62262: Impact Resistance - IK08

ASTM G154: UV - 5000Hrs

UL94: Flammability Rating – 5VA

IEC 62208: Thermal stability - 70°C, 168hrs

IEC 60695: Glow Wire Test - 960°C

CE, RoHS and Reach Complaint

