



Product Info

Brand: Control XL Series

UPC: d9aa0bd5a01f

Carton Quantity: 1

Carton Weight: 20.139 kg

Country of Origin: India

Color: Gray (RAL 7035)

Material: Fiberglass Reinforced Polyester - RTM molded box and cover

Additional Materials: 304 stainless steel external hardware (hinges/latches/fasteners), 304 Stainless Steel Mounting brackets, 304 Stainless Steel internal hardware, Brass inserts, Neoprene gasket

AMXL403212ICCLS

Control XL Series Fibre Reinforced Polyester (FRP) enclosure with stainless Steel 300-Series continuous short hinge with universal Die cast compression cam lock.

Enclosure Type: Wall Cabinets

Cover Type: Opaque

Closure Type: metal snap latch

Mounting Description: Nonmetal feet fastened to back side brass insert

Box Features:

Installation Type:

Height: 1009 mm

Width: 793 mm

Depth: 292 mm

Usable Depth: 290 mm

Volume: 14269 cu mm

Features:

Non-corrosive, non- conductive, UV protected, Flameretardent, Impact resistant, Chemical Resistant, Leight Weight with lower installation cost, Negligible maintenance cost, easy to modify and Loger life cycle compare to Steel/Polycarbonate. Rigid design with Back panel inserts plus Fiberglass Compression molded mounting brackets and Formed-In-Place(FIP) polyurethane gasket on the cover.

Application:

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

Standards:

IEC-62208, IEC-60695-2-11:2000, IEC-60529:2013-08, IEC-60068-2-2:2007, IEC-62262-2002, UL-94 5VA, CE, RoHS Compliant and Reach Compliant.

